

## **D185T4F** POWERFUL + COMPACT



- Curb side controls and service valves for safe operation
- The metal enclosure resists dents and fading, as well as protects major components from job site hazards
- > The new DeepSea controller and Intelligent Start/Stop System prevent cold-starting and blowback
- Kohler's quiet and efficient engine operates without a DEF or DPF
- The standard tool box is positioned to easily place and remove accessories.
- The optional Dual Pressure System allows you to work on applications that need 150 psi

## **OPTIONS**

Dual Pressure System | Hose Reel | Cold Weather Package | Telematics | Skid Support

PORTABLE COMPRESSORS elgi.us/portable



## **D185T4F TECHNICAL DATA**

COMPRESSOR	
Capacity - Pressure (psi)	100 psi (150 psi with Dual Pressure Option)
Capacity - Volume (cfm)	185 cfm (145 cfm with Dual Pressure Option)
Minimum Working Pressure	73 psi
Drive System Engine-Airend	Direct Drive, Twin Screw Rotor
Compressor Cooling System	Air /Oil
Oil Cooling Capacity	2.75 gal
Air Outlet Temperature	105°F Ambient Temperature
Outlet Valves	2 X 3/4"
Battery Capacity	12V 100Ah 790A
Fuel Tank Capacity	23 gal
Fuel Consumption	1.6 gph
Dimensions with Running Gear	L- 124" W- 53" H- 54"
Dry Weight with Running Gear	1,960 lbs
ENGINE	
Engine Make	KOHLER
Engine Type	KDI 1903 TCR
Engine System	4 strokes - High Pressure Common Rail
Displacement	1903 cc
N. Cylinders	3
Aspiration	Turbo Intercooler
Max Engine Power @3000 RPM	49.0 HP
Max Engine Speed	2600 RPM
Min Engine Speed	1700 RPM
Cooling System	Water
Cooling System Capacity	3.70 gal
Lubrication System	Oil
Lubrication System Capacity	2.57 gal
Max Ambient Temperature	122°F
Min Working Temperature	14°F

## SERVICE + SUPPORT

- > 5-Year/Unlimited Hour Airend Warranty
- > 3-Year/4000-Hour Kohler Engine Warranty
- > 1-Year/2000-Hour Full Machine Warranty
- > Parts + Service Help: 704-523-4123 or portableservice@elgi.com



PORTABLE COMPRESSORS elgi.us/portable